SIDE GRIP PILE DRIVERS



SP-50

FEATURES

- Designed to match small to medium size excavators and to combine a robust structure with excellent pile handling characteristics.
- High frequency pile driver with fixed eccentric moment.
- Fitted with heavy-duty arms/clamps capable of driving a wide range of piles including sheet piles, H-piles, tubular steel piles and other pile sections.
- The unit is always equipped with one of the standard arm/clamp systems and the bottom clamp. Customised arms and clamps are available upon special request.
- Controlled with the MOVAX Control System (MCS[™]).
- Available with the MOVAX Information Management System (MIMS[™]).



TECHNICAL DATA

Weight (excl. adapter)	lbs	4,070
Height	in	74
Depth	in	48
Width	in	44
Excavator class	t	25
Engine power, min	hp	168
Return pressure, max	psi	72,5
Pressure setting	psi	4,000
Frequency	1/min	3000
Centrifugal force, max	ton	50
Ground vibration		low
Resonance-free start/stop		no
Driving method		vibration
Swing/tilt angle	o	360 / ± 30

SUITABLE PILES

TYPES AND DIMENSIONS

Sheet piles	width	12"-48"
	depth	12"
H-beams	size	10"-14"
Timber piles	size	14" butt
Tubular piles, tubes	size	13" OD



LENGTH & WEIGHT

20' x 5100 lbs	
40' x 3500 lbs	
40 X 3500 lbs	
50' x 3000 lbs	
20 X 2000 ID2	

www.hmc-us.com // 800