SIDE GRIP PILE DRIVERS

SPM-30

FEATURES

- Designed to match small size excavators and to combine a robust structure with excellent pile handling characteristics.
- High frequency pile driver with fixed eccentric moment.
- Fitted with heavy-duty arms/clamps capable of driving a wide range of piles including sheet piles, H-piles, timber piles, tubular steel piles and other pile selections.
- The unit is always equipped with one of the standard arm/clamp systems and the bottom clamp. Customized arms and clamps are available upon special request.



TECHNICAL DATA

Weight (excl. adapter)	lbs	2738
Height	in	73
Depth	in	42
Width	in	38
Excavator class	t	12-24
Engine power, min	hp	80
Return pressure max	psi	100
Pressure setting	psi	3000
Frequency	1/min	3500
Centrifugal force, max	ton	30
Ground vibration		low
Resonance-free start/stop		no
Driving method		vibration
Swing/tilt angle	٥	360°/15°

SUITABLE PILES

TYPES & DIMENSIONS

Sheet Piles	width	12"-28"
H-beams	size	8"-12"
Timber piles	size	12" butt
Tubular piles, tubes	size	12" OD









LENGTH & WEIGHT

10' x 1500 lbs	20' x 1200 lbs
15' x 1300 lbs	25' x 1100 lbs